



## OMNIKEY® 5427CK Reader



### CONTACTLESS READER WITH CCID AND KEYBOARD WEDGE AVAILABLE WITH BLUETOOTH INTERFACE FOR MOBILE ACCESS

- **Dual frequency** – Simultaneously supports low and high frequency credentials, including iCLASS Seos®, HID Prox®, iCLASS SE®, MIFARE Classic®, MIFARE Plus®, MIFARE Ultralight® and MIFARE® DESFire® EV1, EV2 as well as NFC
- **Supports mobile access** – Available with Bluetooth interface to leverage HID Global's mobile credentials to access computer, network, data or cloud
- **Supports Seos® and iCLASS SE® Platform** – Provides multi-layered security that extends beyond the card technology, offering additional protection to identity data.
- **Ease of use** – Straightforward utilization of existing access control credentials for PC login in both CCID and Keyboard Wedge operation modes
- **Keyboard Wedge support** – Retrieves data from a card and presents the information directly to any application by emulating keyboard strokes.

#### MOBILE ENABLED READER FEATURES:

- Adjustable read settings control overall power and read range of Mobile IDs, enabling flexibility for both close-proximity “tap” and long-range “Twist and Go” distances
- Read settings administered using mobile phone during installation
- Directional antenna enabling long range reading distances up to 2m

HID Global's OMNIKEY® 5427CK Reader operates in virtually any PC environment. Independent of the operating system and use case, the reader's CCID or Keyboard Wedge interface provides the ideal solution with no need to install or maintain drivers. This removes complex software lifecycle management issues in the field and accelerates time to market while allowing the user to become part of the iCLASS SE® platform. The platform offers a secure, standards based technology-independent and flexible solution based on Secure Identity Object (SIO), a new portable and open credential methodology. Thanks to its keyboard wedge functionality, data from the card can be retrieved and transformed for direct input into applications using keystroke emulation and therefore eliminates the need for organizations to manually enter card data into applications. In addition to the standard CCID and Keyboard Wedge operation modes, the reader includes an integrated, easy-to-use web-based management tool that

enables intuitive browser-based configuration without the need for special training. The reader supports two operational modes ensuring long term investment allowing to adapt CCID from keyboard wedge where a change to security requirements appears. The OMNIKEY® 5427CK supports low and high frequency technology within a single device that enables seamless credential migration and mixed technology environments. The reader includes support for a wide range of low and high frequency card technologies, including HID Prox®, Indala® and EM Prox®, MIFARE® Classic, MIFARE DESFire® EV1, EV2 and iCLASS®, as well as iCLASS SE®, iCLASS® Seos™, iCLASS® Elite, and other SIO-enabled credentials. For embedded applications, the OMNIKEY 5427CK is also available as a reader board – dedicated Developer Tool Kit provides all of the necessary tools and documentation to shorten integration cycles and to accelerate time to market with finished products.

**PRODUCT FEATURES:**

**CCID Support**

- Native CCID implementation supporting WINDOWS®, LINUX® and MAC® operating systems.

**Keyboard Wedge**

- Fully configurable and programmable keyboard wedge functionality featuring an integrated management console.
- Flexible configuration of data structures and output modes.
- Human Interface Device (HID) protocol allows reader configuration through host in keyboard Wedge mode
- Extended keyboard boot option for devices with limited USB device handling capabilities

**Broad Credential Support**

- Dual frequency functionality allowing support for both low and high frequency credentials simultaneously.
- HID Prox®, Indala® & EM Prox®, MIFARE® Classic, MIFARE DESFire® EV1, EV2, iCLASS®, iCLASS SE®, iCLASS® Seos™, iCLASS® Elite, and other SIO enabled credentials.
- Available with Bluetooth interface to be used with HID mobile access credential for IT Access

**Enhanced Lifecycle Management**

- Easy firmware updates and configuration setting utilizing a Web interface, SNMP messages and configuration cards.
- Developer Tool Kit (DTK) available that contains product samples, development documentation, samples code and access to HID Global's developer portal.



**KEYBOARD WEDGE FEATURES INCLUDE:**

- Configurable input & definable output fields per output field
- Cascadeable free custom data fields
- Card-specific configurations
- Pre- / poststroke definitions and shortcuts
- Big / Little Endian Conversion
- HEX, BCD, BIN, DEC & ASCII output transformation
- Bitstream parsing of HID's Physical Access Control
- Data filtering and padding of leading / trailing characters
- Reverse output incl. custom, CSN and PACS data objects



**SPECIFICATIONS**

13.56 MHz HF and 125Khz LF Smart Card Reader with CCID and Keyboard Wedge Interface		
Base Model Number	OMNIKEY® 5427CK Gen2	
Bluetooth functionality	WITH BLUETOOTH	WITHOUT BLUETOOTH
<b>Contactless Smart Card Interface</b>		
<b>Protocols and Cards HF</b>	T=CL, MIFARE®, iCLASS® ISO 14443A/B - up to 848 kbps (depending on card) iCLASS SE and Seos (can read data only / no writing) Felica (only UID) NFC Tag (1, 2, 3, 4, 5)	T=CL, MIFARE®, iCLASS® ISO 14443A/B - up to 848 kbps (depending on card) iCLASS SE and Seos (can read data only / no writing) Felica (only UID) NFC Tag (1, 2, 3, 4, 5)
<b>Protocols and Card LF</b>	HID Prox (FSK) Indala (PSK) EM 41xx (ASK) Hitag 1, 2, S (Hitag)	HID Prox (FSK) Indala (PSK) EM 41xx (ASK) Hitag 1, 2, S (Hitag)
<b>Bluetooth Interface</b>		
<b>Supported Functions</b>	HID Global Mobile Access Service	
<b>Host Interface</b>		
<b>USB Interface</b>	USB 2.0 Full Speed Device (12 Mbps) USB 3.0 extended operability, tested with hubs/controllers	USB 2.0 Full Speed Device (12 Mbps) USB 3.0 extended operability, tested with hubs/controllers
<b>Connector / Cable</b>	USB Type A connector; 59.1" (150 cm) cable	USB Type A connector; 59.1" (150 cm) cable
<b>Operating Systems</b>	Windows 10/8.1/8/7/Server 2016/Server 2012/Server 2008R2 Linux Debian 6.0+ / Ubuntu 11.04+ / Fedora 15+; Open SUSE 11.4+ Mac OS X**; Android™ 4.x to 9.x**	Windows 10/8.1/8/7/Server 2016/Server 2012/Server 2008R2 Linux Debian 6.0+ / Ubuntu 11.04+ / Fedora 15+; Open SUSE 11.4+ Mac OS X**; Android™ 4.x to 9.x**
<b>PC/SC Driver</b>	CCID native driver from operating system (Windows/Linux/Mac)	CCID native driver from operating system (Windows/Linux/Mac)
<b>Keyboard Driver</b>	Native driver from operating system supporting MF-102 keyboard (Windows/Linux/Mac)	Native driver from operating system supporting MF-102 keyboard (Windows/Linux/Mac)
<b>Supported APIs</b>	PC/SC - API, SAM - API	PC/SC - API, SAM - API
<b>Human Interface</b>		
<b>Status Indicator</b>	Dual Colour Led (White + Blue)	Dual Colour Led (White + Blue)
<b>Housing</b>		
<b>Housing</b>	Poly Carbonate Cover Black / Body Light Grey Card Holder for card presence operation	Poly Carbonate Cover Black / Body Light Grey Card Holder for card presence operation
<b>Dimensions</b>	2.79" x 3.66" x 0.63" (71 mm x 93 mm x 16 mm)	2.79" x 3.66" x 0.63" (71 mm x 93 mm x 16 mm)
<b>Weight</b>	-100 g (3.53 oz)	-100 g (3.53 oz)
<b>Operating Conditions</b>		
<b>Operating Temperature</b>	32° - 131° F (0° - 55°C)	32° - 131° F (0° - 55°C)
<b>Operating Humidity</b>	10 - 95% rH (not condensing)	10-95% rH (not condensing)
<b>Storage Temperature</b>	-4° - 176° F (-20° - 80°C)	-4° - 176° F (-20° - 80°C)
<b>Meantime Between Failure (MTBF)</b>	500.000 hours	500.000 hours
<b>Compliance and Regulatory</b>		
<b>Compliance / Certification</b>	USB 2.0	USB 2.0
<b>Regional certifications</b>	CE, FCC, UL, KCC, RCM	CE, FCC, UL, KCC, RCM
<b>Environmental</b>	WEEE, RoHS3, Reach	WEEE, RoHS3, Reach
<b>Ordering Information</b>		
<b>Warranty</b>	Two-year manufacturer's warranty	Two-year manufacturer's warranty
<b>Optional</b>	Mounting accessories kit	Mounting accessories kit

\* reader/writer mode only; NDEF format to be implemented by additional software  
\*\* CCID and KeyBoard Wedge support

**hidglobal.com**

North America: +1 512 776 9000  
Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 5081 1650

© 2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, OMNIKEY, iCLASS, iCLASS SE, iCLASS Seos, iCLASS Elite, HID Prox, Indala, Secure Identity Object, SIO and HID Prox are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
2019-08-09-omnikey-5427-ck-reader-ds-en PLT-00389